

Connecting devices

Connecting and junction boxes BJK/S and BJK/RR

Halogen free Polycarbonate box - IP 66 (CEI 529)
Knock out Input / temperature range : -40°C / + 80°C
model BJK/S : 130*130*74 mm
model BJK/RR : 175*130*74 mm
Mobile terminals and power gland included



Quick connectors P & T CONNECT

P-CONNECT : for extension junction
IP 68 (Dmaxi = 35 mm).
T-CONNECT : for T junction box IP 65
temperature range : -20°C / +125°C
section : mini : 1.00 mm² / maxi 2.50 mm²
connexion blocks and washers included.



ATEX connexion box BJE/Ex"e" for hazardous area

Increase security connexion box
II C T6 (85°C) - Ex "e" Graphitized Polycarbonate
4 holes M 20 + 3 plugs M20 / 1 power gland M20.
IP 66 / Maxi current 10 A / 230 V / maxi section: 2.50 mm²
DIN rail + 4 bridge terminals
+ 2 ground terminals / 120*120*92 mm



ATEX explosion proof connexion box BJD/Ex"d" for hazardous area

Explosion proof box
for hazardous area
II C T6 (85°C) - EEx "d" - cast iron
3 holes 3/4" NPT + 1 plug

